



MACHINE SPECIFICATIONS

MACHINE VOLTAGE	480V-3PH-60HZ
EST AMP LOAD	38 AMPS @ 480V
MAIN DISCONNECT	60 AMP FUSED 40 AMP
EST GLUE AMP LOAD	10 AMPS @ 480V
GLUE DISCONNECT	30 AMP FUSED 15 AMP
EST AIR USE	22 SCFM @ 90PSI
MACHINE ELEVATION	45.25" MACHINE ELEVATION MIN 43.25" MAX 47.25"

1 TIPPED PRODUCT RESET INFEED JOG & METERING MANUAL CYCLE BUTTONS

2 MAGAZINE LOAD AREA

D	3/7/2014	BAJ	CORRECT EST AIR USE SPEC 22 SCFM WAS 1; UPDATE HOTMELT APPLICATOR	JG	JG
C	12/02/2013	BAJ	UPDATE FOR PRODUCTION PER SOLID MODEL; (ELEVATION 45.25" WAS 53.25")	JH	JH
B	8/16/2013	BAJ	REMOVE DYNAMIC TRANSFER CONVEYOR	JH	JH
A	8/9/2013	BAJ	RELEASE PRELIM FLOORPLAN	JR	
REV.	DATE	REVISED BY	CHANGE DESCRIPTION	REQUESTED BY	APPROVED BY

Douglas Machine Inc.
3404 Long Street
Alexandria, MN 55305 USA
TEL: 1-800-763-6587
FAX: 1-800-763-5754
URL: www.douglas-machine.com

DRAWING NAME: MARS PETCARE CONTOUR SERIES T105 FLOOR PLAN LH-MAIN LH-INFEED					
DRAWN BY: BJ	CREATION DATE: 08/08/2013	SCALE: 1:48	PDM T.D.	SHEET: 1 of 1	
PROJECT NO: M313029	DWG SZ: C	DRAWING NO: 130674FPD			

This drawing and the information contained is the sole property of Douglas Machine Inc. It is not to be used, copied, reproduced, or distributed in whole or in part without the prior written consent of Douglas Machine Inc.